

ENERGY EFFICIENCY

Thermal Transmission Coefficient
Ucw ≥ 0.6 (W/m²K)

Please consult typology, dimensions and glazing

GLAZING

Maximum glazing: **64 mm**

Minimum glazing: **4 mm**

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN 12152):

Water tightness (EN 12154):

Wind resistance (EN 13116):

Reference test 3.00 x 3.50 m

Class AE

Class RE1350

PASSED Design loading 2000 Pa-Security loading 3000 Pa

PROFILE THICKNESS	Mullion 2,1 and 3 mm Transom 2,1 mm	EXTRUSION ALLOY	6063 T-5
WINDOW MAXIMUM DIMENSIONS	<p>Hidden Top Hung Width max. (L) = 2.500 mm Height max. (H) = 2.500 mm Width min. (L) = 500 mm Height min. (H) = 650 mm</p> <p>Hidden Parallel Projecting Width max. (L) = 1.500 mm Height max. (H) = 3.000 mm Width min. (L) = 450 mm Height min. (H) = 530 mm</p> <p>Hidden Side Hung or Turn&Tilt Width máx. (L) = 1.400 mm Height máx. (H) = 1.900 mm Width min. (L) = 500 mm Height min. (H) = 600 mm</p>	THERMAL BREAK	6, 12 and 30 mm stackable profiles
MAXIMUM WEIGHT	<p>200 kg Parallel projecting opening 180 kg Hidden top hung opening 100 Kg Tilt & turn opening 750 Kg Fixed glazing</p>	GASKETS EPDM	Optionally Totally Vulcanized Corner Gasket
		OPTIONS FOR COVERS	<p>85 mm deep elliptical cover H shape cover, 34 mm deep Rectangular cover: 14, 19, 100 & 145 mm deep Flat cover Pyramid shape cover, 155 mm deep</p>
		OPENING POSIBILITIES	<p>Outward: Hidden top hung Hidden parallel projecting Inward: Hidden side hung / tilt & turn</p>

Please consult maximum dimensions according to types

FINISHES

Colour powder coating
(RAL, mottled, rough...)

According to Qualicoat Standard > 60 microns

Wood effect powder coating

According to Qualideco Standard

Anodized

According to Ewwa Euras Standard

Standard Class 15

Optionally Class 20 and 25

Optionally bicoloured



Certification CWCT.
British Standard

