



COR 70 HIDDEN SASH C16 ST

TBB

ENERGY EFFICIENCY

Thermal Transmission Coefficient

$U_w \geq 1,0$ (W/m²K)

Please consult typology, dimensions and glazing.

ACCOUSTIC INSULATION

Maximum glazing fixed: **40 mm**

Maximum glazing window: **38 mm**

Maximum acoustic insulation: **Rw = 45 dBA**

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN 12207):

Class 4

Water tightness (EN 12208):

Class E1200

Wind resistance (EN 12210):

Class C5

Reference test window 1.23 x 1.48 m 2 sashes

SECTIONS	Frame 70 mm Sash 70 mm
PROFILE THICKNESS	Window 1.6 mm
MAXIMUM DIMENSIONS	Width (L) = 1.300 mm Height (H) = 2.400 mm
MAXIMUM WEIGHT/SASH	150 Kg

Please consult maximum dimensions according to types.

FINISHES	Colour powder coating (RAL, mottled, rough...) According to Qualicoat > 60 microns Wood effect powder coating According to Qualideco standard Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25 Optionally bicoloured
----------	--

EXTRUSION ALLOY
6063 T-5

POLYAMIDE STRIP LENGTH
Polyamide 6,6 reinforced with 25% fiberglass : Frame 35 mm Sash 30 mm

GASKETS
EPDM triple gasket

FOAMS
Perimeter polyolefin foam in glazing rebate zone

OPENING POSIBILITIES
INWARDS Casement, tilt & turn, tilt.

CERTIFICATES
DTA certification from CSTB lab

