

## ENERGY EFFICIENCY

Thermal Transmission Coefficient

**Uw ≥ 0.7 (W/m²K)**

Please consult typology, dimensions and glazing

## ACCOUSTIC INSULATION

Maximum glazing: **73 mm**

Maximum acoustic insulation: **Rw = 46 dB**

## CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN 12207):

Water tightness (EN 12208):

Wind resistance (EN 12210):

Burglar resistance (EN 1627):

Reference test 1.23 x 1.48 m / 2 sashes

**Class 4**

**Class E1950**

**Class C5**

**Grade RC2 (WK2)**

SECTIONS	Frame 80 mm Sash 88 mm
PROFILE THICKNESS	Window 1.5 mm Balcony 1.6 mm
MAXIMUM DIMENSIONS	Width (L) = 1.500 mm Height (H) = 2.600 mm
MAXIMUM WEIGHT/SASH	160 Kg

Please consult regarding maximum weight and dimensions according to types

FINISHES	<p>Colour powder coating (RAL, mottled, rough...) According to Qualicoat &gt;60 microns</p> <p>Wood effect powder coating According to Qualideco standard</p> <p>Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25</p> <p>Optionally bicoloured</p>
----------	---


EXTRUSION ALLOY	6063 T-5
-----------------	----------

POLYAMIDE STRIP LENGTH	Polyamide 6.6 reinforced with 25% fiberglass: 45 mm
------------------------	--

GASKETS	EPDM triple gasket
---------	--------------------

FOAMS	Perimeter polyolefin foam in glazing rebate zone
-------	--

OPENING POSSIBILITIES	
INWARD	Side hung, tilt & turn, tilt & paralleland, bottom hung
OUTWARD	Side hung and top hung projecting

CERTIFICATES	
Burglar resistance - Grade RC2	
Certification ATG - 3204	